

## Model 1960

Model 1960 is a viewing window constructed for all environments – from high humidity normal temp to low temp applications. Newly designed with a vinyl insulating back frame section, it can be used ENERGY-FREE for most normal temp applications, but perimeter frame heat and glass heat are also available to accommodate extremes in climate conditions.

The heavy-duty, expandable, and interlocking 2-piece frame adjusts to wall thickness from 2 5/16" to 6", and allows for large net openings – with a maximum limitation of 25 square feet.

Model 1960 Viewing Windows are available in Smooth silver, Satin silver anodized, and Black finishes.

	Glass Size (Sq. Ft.)	List Price	Price for Each Add'l Sq. Ft.
<b>Normal Temp:</b> <b>2PNHG</b> <b><u>2-Pane Non-htd</u></b>	1	\$ 252	\$ 47
	4	\$ 399	\$ 42
	9	\$ 614	\$ 21
	16	\$ 756	\$ 18
	25	\$ 919	\$ 17
<b>Normal Temp:</b> <b>CP2NT</b> <b><u>2-Pane Heated</u></b>	1	\$ 368	\$ 74
	4	\$ 588	\$ 53
	9	\$ 851	\$ 34
	16	\$ 1,092	\$ 22
<b>Normal Temp:</b> <b>3PNHG</b> <b><u>3-Pane Non-htd</u></b>	1	\$ 294	\$ 58
	4	\$ 462	\$ 49
	9	\$ 709	\$ 32
	16	\$ 924	\$ 28
	25	\$ 1,181	\$ 24
<b>Low Temp:</b> <b>CP3LT</b> <b><u>3-Pane Heated</u></b>	1	\$ 420	\$ 84
	4	\$ 672	\$ 63
	9	\$ 992	\$ 37
	16	\$ 1,260	\$ 32

Note: When ordering, specify maximum thickness of installation wall. Net openings must be square and precise to tolerance of -0 + 1/8". All prices are subject to change without notice.

## Model 1950

Model 1950 is a double frame Viewing Window that is shipped ready to install, manufactured to customer specifications for cooler or freezer applications. Heated or non-heated perimeter frames and glass are available. These units are installed in pre-cut wall openings, therefore no modifications are necessary, and no additional parts or special tools are required. (Maximum limitation of 16 square feet.)

Model 1950 Viewing Windows are available in Smooth and Serrated gold anodized, Smooth and Serrated polished silver, Smooth silver satin anodized, and Black finishes.

*Custom pricing for individual customer specifications – please call the factory for a quote.*

*Note: When ordering, specify maximum thickness of installation wall. Net openings must be square and precise to tolerance of  $-0 +1/8$ ". Panels for Model 1950 not covered by tempered glass or hermetic seal warranties.*

Anthony products are covered by one or more of the following United States Patents: RE35,120; 4,905,347; 5,309,066; 5,315,211; 5,284,371; 5,605,237; 4,671,582; 4,696,078; 4,760,621; 5,002,320; RE35,149; 5,251,402; 5,297,863; 5,299,437; D332,564; RE35,392; 5,301,092; 5,363,611; 5,544,454; 5,720,540; 5,879,070; 5,895,111; 5,910,083; 6,029,411; 6,031,338; 5,902,034; 5,959,816; 6,010,227; 6,122,869; 6,222,322; 6,260,255; 6,298,615; 6,302,036; 6,302,557; 6,318,027; 6,325,523; 6,367,223; 6,389,993; 6,490,983; 6,343,405; 2,987,782; 3,131,421; 3,295,634; 3,345,606; 3,399,784; 3,449,551; 3,475,594; 3,499,245; 3,508,361; 3,526,753; 3,629,972; 3,673,735; 3,696,360; 3,697,723; 3,837,119; 4,145,844; 4,261,179; 4,416,086; 4,428,096; 4,430,770; 4,641,461; 4,656,781; 4,691,486; 4,741,127; 4,753,043; 4,831,780; 4,852,303; 4,941,289; 4,998,382; 5,016,146; 5,024,023; 5,035,085; 5,116,274; 5,207,490; 5,214,877; 5,244,273; 5,255,473; 5,333,355; 5,111,618; 5,471,372; 5,622,414; 5,645,330; 4,004,370; 4,035,608; 4,080,756; 4,087,139; 4,127,188; 4,127,765; 4,221,443; 4,248,015; 4,260,876; 4,265,069; 4,306,140; 4,382,177; 4,477,129; 5,097,642; 5,113,628; 5,116,274; 5,207,490; 5,622,414; 4,691,486. Corresponding Foreign Patents Issued. Other United States and Foreign Patents Pending.

### **ANTHONY INTERNATIONAL**

(818) 365-9451   (800) 772-0900   [Canada (800) 336-8825]   Fax (818) 361-9611  
 12391 Montero Avenue, Sylmar, CA 91342   www.anthonydoors.com